

Diesel Smoke Stop Concentrate

Description

Diesel Smoke Stop (C) is a highly effective diesel fuel additive that delivers an important contemporary impact. The product reduces soot emissions from diesel engines by accelerated soot combustion. Diesel Smoke Stop considerably improves the environmental compatibility of diesel passenger cars and trucks and prevents odor pollution and impairment of visibility. Diesel Smoke Stop maintains engine performance and reduces the frequency of repairs.

Properties

- no smell
- protects the environment
- improves the turbidity value
- keeps injection nozzles clean
- reduces soot emissions
- assures a clear view and safety
- does not contain heavy metals
- high engine cleanliness
- good corrosion protection
- self mixing
- prevents seizing and the injector needles from gumming up

Technical data

Base	additive mixture in carrier fluid
Color / appearance	brown, dark
Density at 15 °C	0,7981 g/cm ³
Flash point	>63 °C
Form	liquid
Viscosity at 40 °C	<7 mm ² /s
Odor	characteristic

Areas of application

For all diesel engines, for agricultural and forestry as well as stationary diesel engines.

Application

250 ml of Diesel Smoke Stop for 200 liters of diesel fuel. Pour the contents of the can into the tank before filling up with fuel.

Available pack sizes

250 ml Can sheet metal	2521
	D-E-P
250 ml Can sheet metal	7179
	GB-GR-I
250 ml Can sheet metal	8368
	GB-ARAB-F

Available pack sizes

205 l Drum sheet metal	2519
	D-GB

Our information is based on thorough research and may be considered reliable, although not legally binding.

