

Description

Low-friction motor oil based on synthetic technology. Reliably prevents the formation of deposits, has extremely high shear stability, reduces frictional losses in the engine and provides outstanding protection against wear. Ideal for modern gasoline and diesel engines with and without multi-valve technology, Valvetronic and turbocharging (with or without diesel particulate filter (DPF) and charge air cooling). Especially suitable where there are long intervals between oil changes and heavy duty engine requirements.

Properties

- optimum stability to aging
- high lubrication reliability
- instant lubrication after cold start
- tested for turbochargers and catalytic converters
- high engine cleanliness
- saves fuel and reduces pollutant emissions
- high shear stability

Specifications and approvals

ACEA A5 • ACEA B5 • Ford WSS-M2C 913-D • Jaguar / Land Rover STJLR.03.5003

LIQUI MOLY also recommends this product for vehicles or assemblies for which the following specifications or original part numbers are required

Fiat 9.55535-G1 • Ford WSS-M2C 913-A • Ford WSS-M2C 913-B • Ford WSS-M2C 913-C • IVECO 18-1811 S1

Technical data

SAE class (engine oils)	5W-30 SAE J300
Density at 15 °C	0,855 g/cm ³ DIN 51757
Viscosity at 40 °C	52,4 mm ² /s ASTM D 7042-04
Viscosity at 100 °C	9,9 mm ² /s ASTM D 7042-04
Viscosity at -35 °C (MRV)	< 60000 mPas ASTM D4684
Viscosity at -30 °C (CCS)	≤ 6600 mPas ASTM D5293
Viscosity index	179 DIN ISO 2909
HTHS at 150°C	2,9 - 3,5 mPas ASTM D5481



Technical data

Flash point	220 °C DIN ISO 2592
Pour point	-42 °C DIN ISO 3016
Evaporation loss (Noack)	12 % CEC-L-40-A-93
Total base number	11,1 mg KOH/g DIN ISO 3771
Sulfate ash	0,85 g/100g DIN 51575
Color number (ASTM)	L3,5 DIN ISO 2049

Areas of application

The latest specification from Ford (WSS-M2C 913-D) is primarily required for various vehicle types from 2011. Backwards compatible and can be used without hesitation in older Ford vehicles from 7/1998. Also suitable for vehicles from various other manufacturers. Tested for use with turbochargers and catalytic converters. **Not suitable for VW with extended maintenance intervals (WIV)!**

Application

The specifications and instructions from the assembly or vehicle manufacturer must be followed!

Available pack sizes

1 l Canister plastic	2325 BOOKLET
1 l Canister plastic	21240 ALGERIEN-GB-ARAB-F
5 l Canister plastic	2326 BOOKLET
5 l Canister plastic	21232 ALGERIEN-GB-ARAB-F
20 l Canister plastic	3854 D-GB-I-E-P
60 l Drum sheet metal	3856 D-GB

Product information

PI 29/09/21/2021



Available pack sizes

205 l Drum sheet metal 3857
D-GB

**Our information is based on thorough research
and may be considered reliable, although not
legally binding.**