

## Lawnmower Oil SAE 30

### Description

Single-grade motor oil with high-quality base oils and high additive content. Ensures first-class lubrication, optimum engine cleanliness, outstanding wear protection and a long service life of the lawnmower engine. Also provides reliable protection against corrosion under adverse conditions and when overwintering. Tested on engines with catalytic converters.

### Properties

- low evaporation loss
- miscible with all commercially available motor oils
- high wear resistance
- tested for the use with catalytic converters
- excellent cleaning effect
- very good dispersion properties
- high resistance to aging
- outstanding lubricating action

### Specifications and approvals

API SJ

### Technical data

SAE class (engine oils)	30 SAE J300
Density at 15 °C	0,875 g/cm <sup>3</sup> DIN 51757
Viscosity at 40 °C	90 mm <sup>2</sup> /s ASTM D 7042-04
Viscosity at 100 °C	11,6 mm <sup>2</sup> /s ASTM D 7042-04
Viscosity index	115 DIN ISO 2909
Pour point	-33 °C DIN ISO 2592
Evaporation loss (Noack)	6,8 % ASTM D 5800-08 Method B
Flash point	230 °C DIN ISO 3016
Total base number	11 mg KOH/g DIN ISO 3771
Sulfate ash	1,2 g/100g DIN 51575
Color number (ASTM)	4 DIN ISO 2049

### Areas of application

For 4-stroke lawnmower engines, emergency power



units and other engines that require a single-grade motor oil with viscosity class SAE 30 and the existing specifications.

### Application

The specifications and instructions from the assembly or equipment manufacturer must be followed.

### Available pack sizes

1 l Canister plastic	1264 D-BOOKLET
5 l Canister plastic	1266 D-BOOKLET

**Our information is based on thorough research and may be considered reliable, although not legally binding.**