

## Motorbike Radiator Stop Leak

### Description

Dispersion for sealing leaks in coolant circuits. The product reliably seals hairline cracks and small leaks. Can be used preventively when repair work has been carried out on the cooling system. The solids dispersion is stabilized in carrier fluid.

### Properties

- compatible with conventional coolants and antifreezes
- permanently and reliably seals hairline cracks and small leaks
- no harmful side effects
- suitable for aluminum radiators

and may be considered reliable, although not legally binding.



### Technical data

Form	liquid
Color / appearance	white, cloudy
Density at 20 °C	1,05 g/cm <sup>3</sup>
Solubility in water	mixable
Odor	weak
Flash point	>100 °C

### Areas of application

For sealing minor leaks in coolant systems with and without coolant filter. Also suitable for aluminium and plastic radiators.

### Comment

Store free of frost.

The treated product contains biocides as protective agents. Contains a mixture of: 5-chloro-2-methyl-2H-isothiazol-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1).

### Application

Shake well before use. Add contents to the cold cooling system. Then drive the vehicle for at least 10 minutes. Contents will treat up to 5 liters of coolant.

### Available pack sizes

125 ml Can sheet metal	5924
	D-F-I-GR
125 ml Can sheet metal	3043
	D-GB-E

### Our information is based on thorough research