

Octane Plus

Description

Self-mixing combination of agents formulated according to state-of-the-art additive and fuel technology. Universal use. Increases the research octane number (RON) of the fuel by 2-4 points, depending on the RON. Thanks to the increased performance of the fuel, engine damage caused by knocking combustion is prevented. The increase of the octane number ensures low fuel consumption.

Properties

- improves performance
- increases the octane number
- prevents engine damage caused by knocking combustion

Technical data

Color / appearance	brown, clear
Base	additives, naphtha
Density at 15 °C	0,817 g/cm ³
Flash point	63 °C
Pour point	-45 °C
Viscosity at 40 °C	< 7,0 mm ² /s
Odor	characteristic
Form	liquid

Areas of application

For increasing the octane number of gasoline.

Comment

IMPORTANT: Only available for order outside Europe.

Application

One 150 ml can is sufficient for 50 l gasoline. Increases the RON by up to 4 points. Pour Octane Plus into the fuel tank and then top up with fuel. Mixing takes place automatically. Minimum fuel filling of 7 gal. is requested for optimum product performance.

Note: Do not store the product at temperatures > 40 °C for extended periods!

Available pack sizes

150 ml Can sheet metal	8351 GB-ARAB-F
150 ml Can sheet metal	2956 GB-GR-I
150 ml Can sheet metal	8355 D-E-P
150 ml Can sheet metal	7144 ALGERIEN-GB-ARAB-F
150 ml Can sheet metal	20879 JP



Available pack sizes

150 ml Can sheet metal	21349 D-GB-CN
200 l Drum sheet metal	8858 D-GB

Our information is based on thorough research and may be considered reliable, although not legally binding.