

Description

LIQUI MOLY central hydraulic system oils meet the highest technical requirements and are suitable for a wide range of automotive applications. The carefully selected formulations made from the best raw materials ensure excellent temperature properties and guarantee the full function of the systems even at the lowest temperatures of up to -45 °C. All central hydraulic system oils are impressive thanks to excellent wear, aging and corrosion protection as well as optimum friction values and minimal foaming tendency.

Properties

- excellent viscosity/temperature properties
- optimum stability to aging
- highest thermal stability
- excellent low temperature behavior
- outstanding corrosion protection

LIQUI MOLY also recommends this product for vehicles or assemblies for which the following specifications or original part numbers are required

BMW 81 22 9 407 758 • Fiat 9.55550-AG3 • Ford WSS-M2C 204-A • MAN M 3289 • MB 345.0 • Opel 1940 766 • VW G 002 000 • VW G 004 000 • ZF TE-ML 02K

Technical data

| Viscosity at 40 °C | 19,5 mm²/s ASTM D 7042-04 |
|-----------------------------|------------------------------|
| Viscosity at 100 °C | 6,1 mm²/s ASTM D 7042-04 |
| Viscosity index | 300 DIN ISO 2909 |
| Color / appearance | green |
| Density at 15 °C | 0,825 g/cm³ DIN 51757 |
| Flash point | 150 °C DIN ISO 2592 |
| Pour point | -51 °C DIN ISO 3016 |
| Foaming behavior at 24 °C | 50/0 ml ISO 6247 |
| Foaming behavior at 93.5 °C | 35/0 ml ISO 6247 |

Areas of application

This synthetic hydraulic fluid with ash-free additives is ideally suited for steering systems, electro-hydraulic convertible tops, level controls, hydropneumatic suspensions, damping systems, cab tilting devices,



etc.

Application

The specifications and instructions from the assembly or vehicle manufacturer must be followed. This oil can also be used for refilling in systems. Optimum effect only when the product is used unmixed.

Available pack sizes

| 1 l Can plastic | 1158 D-NL-F-GR-ARAB |
|-------------------------|-----------------------------|
| 1 l Can plastic | 1127 D-GB-I-E-P |
| 1 l Can plastic | 20468 PL-H-RO-TR |
| 1 l Can plastic | 2366 GB-DK-FIN-N-S |
| 1 l Can plastic | 9524 D-GB-F-ARAB |
| 1 l Can plastic | 21239 ALGERIEN-GB-ARAB-F |
| 20 l Canister plastic | 1147 D-GB-I-E-P |
| 60 l Black plate barrel | 1148 D-GB |

Our information is based on thorough research and may be considered reliable, although not legally binding.