

Molygen Motor Protect

Description

Synthetic and oil-soluble engine-oil additive which has been developed according to the latest technology for use in modern gasoline and diesel engines. The surface active components of this high-pressure/anti-wear additive in combination with new friction modifiers reduce mechanical wear and friction by modifying the surfaces.

Properties

- reduces fuel consumption
- friction and wear reducing
- stable under extreme pressures
- increases smooth operation
- tested for particulate filters and catalytic converters
- high thermal stability
- miscible with all commercially available motor oils
- long engine service life

Technical data

Base	synthetic additives, base oils
Color / appearance	green
Density at 20 °C	0,877 g/cm ³
Viscosity at 40 °C	120,92 mm ² /s DIN 51398

Areas of application

For gasoline and diesel engines.
Not suitable for use on motorbikes with wet clutches.

Application

Molygen Motor Protect should be added approximately every 50,000 km during oil changes. Can contents are sufficient for up to 5 litres oil. Reduce the specified oil volume by 500 ml. For the sake of economy, the product should be added during or shortly after oil changes. Molygen Motor Protect is compatible with all commercially available mineral-based and synthetic-based engine oils.

Note:

Not suitable for use with wet clutches!

Available pack sizes

500 ml Can sheet metal	1789 KOREA-D-GB-NL-F-E-I
500 ml Can sheet metal	1015 D-GB-NL-F-E-I

Our information is based on thorough research



and may be considered reliable, although not legally binding.